
Carif 450 BSA VAR-E

SEMI-AUTOMATIC COMPLETELY HYDRAULIC BAND SAW



6



Standard Features:

- 1. Robust base structure (5mm) in steel powder painted with bright and smooth finishing.
- 2. Robust head structure made in one unique piece of structural steel.
- 3. Patented Hydraulic system for a fine regulation of bow feed and cutting pressure for any kind of material.
- 4. Electronic speed variator Kw 4; speed range 15÷100 m/1'.
- 5. Miter cutting -45°/+60°; bow rotation through conical bearings independent from the plans for piece support.
- 6. Swing Arm Console with Integrated Panel to control Blade Speed, Cutting Height & Piece Counter.
- 7. Wide Plans for piece support for a comfortable and practical cutting area.
- 8. Complete coolant equipment of 50 lt. tank with electro-pump 3ph. inside the basement
- 9. Measuring device L=500 mm with height regulation.
- 10. Sensor for monitoring blade rotation.
- 11. Eccentric roller for short piece cutting.
- 12. Potentiometer to memorize cutting height.
- Large chips container for easy cleaning.
- Bimetal blade M42 mm 3660x34x1,1, cardboard box + pallet, service wrenches, instruction manual and spare parts list

CUTTING CAPACITY

90°	-45°	+45°	+60°	+90°	-45°	+45°	+60°	+90°▲	-45°	+45°	+60°	90° opt.
330	260	280	170	320*/ 280	220	250	150	450 x 240	310 x 100	270 x 240	170 x 125	450 x 240
* With thickness										LxH		

TECHNICAL FEATURES

m	KW	[m/1']			Kg	B +- L+		+ H + H + H + H	
mm	KW	m/1'	mm	Optional	Kg	В	L	н	h
3660x34x1,1	4	15÷100	450	500	1100	2050	1180	2000 / 1550	830

450 BSA VAR-E CASIF

Optional

- 1. Air/oil lubrication system 3lt. 2 elements
- 2. Digital angle integrated in the front display
- 3. Laser-line for positioning
- 4. Hydraulic device for vertical clamping of bars (1 Piece)
- 5. Additional double vice (for specific cutting)
- 6. Working LED light
- 7. Flushing hose
- ▲ Thickness for cutting at 90° (mm 500 x 190 h)















Roller units

Modular roller-unit type "A":

length 1m - width 500 mm - capacity 3 t/m

Modular roller-unit type "B":

length 1m - width 500 mm - capacity 3 t/m

Plan type "C" for connection roller-unit type "A" to the machine : width 500 mm

Measuring Device

Measuring device graduated in mm type "D": L = 1 meter

CARIF MS - Measuring System: L = 2-3-4-... meters

CARIF DMS - Digital Measuring System: L = 2-3-4-... meters

